

PRODUCT DESCRIPTION

Q-PAINT is premium acrylic-based emulsion paint for interior wall surfaces, provides exception paint durability and performance.

PRODUCT USES

- Prepaire the surface free from any sand, dirt, and grease, Ensure surface to be smooth.
- Using a staff fibre bush of high presure water jet, Remove all loose paint & powdery residue.
- Eliminat mould, lichen algae and moss on walls with fungicidal wash, if the wall remains chalky or powdery apply C-Plast on the wall 2 or 3 coat and a coat of Wall Stick for internal wall.
- Don't apply during wet weather, Ensure moisture levels within walls are of acceptable levels before painting.
- Applied thickness 240 microns per coat

PHYSICAL DATA

Finish	Flat
Color	Assorted colors
Application for	Concrete, cement, mortar
Components	1
Volume solids	72% by weight(White)
Recommended dry film thickness	55μm
Coats	2-3
Thoretical coverage	5-6m²/L (@D.F.T 55µm)
Dryling times at 25°C	
Dry through	2.5 hr
Dry to recoat	After 3.5hrs
Thinning ratio	Within 5% (by volume)
Thinner	Water
Shelf life	1 Year from manufacture's date when stored indoors at 5-38°C

SEMI-GLOSS EMULSION COATINGS, PURE ACRYLIC-BASED EMULSION **PAINT Q-PAINT (INTERNAL)**

FEATURES AND BENEFITS

- . Q-PAINT is designed specially to protect unsinghtly wall against fungus weather.
- . O-PAINT is high performance anticarbonation formulation keeps walls protect.
- . Q-PAINT is also equiped with color, which helps preserves wall colours, keeping them fresh and vibrant for a longer period of time. Saffer for your family and for the environment.
- . Anti Algae, Anti Fungus, Easy clearn and dry from dirt.

HEALTH AND SAFETY

- Keep away from food, drinks and animal
- When applying paints, it's advisable to wear eye protection
- Keep reach out from Children
- Don't apply if the temperature is below 5°C.
- Don't freeze unused paint products.
- To remove splashes pf paint from skin, use water or a re-cognised cleaner.
- Don't empty into drains or water course paints should not be used for painting any part the body.

STORAGE AND SHELF LIFE

- . Store all materials in a cool dry place, in an elevated condition.
- . 12 months in the original unopened container. Store at above 5°C and dry place

PACKAGING O-PAINT 25/5US GallonS

Paint

Disclaimer. All representations and recommendations set forth are given in good faith and the best of our knowledge. However due to varying conditions and applications the buyer shall conduct its own tests of this product before use. Under no circumstances will the manufacturer be liable for any loss or damages caused by incorrect usage. The sale of this product shall be on terms and conditions set forth on BOTICA's order acknowledgement