



PRODUCT DESCRIPTION

BOTICA Water-Shield is pure Acrylic silicon based paint with special formulated for water-proof paint, Nano Paint, Low VOC, Low odour and suitable for exterior and interior walls to protect the exterior surfaces. It's provide more than 2,500 colours UV protect, dirt pick up, hair crack , Alkali, Algae, Fungus resistance and reduce temperature 20% to 30%.

STANDARD APPROVAL

Approved by TUV from Singapore 2010.

PHYSICAL DATA

Finish	Flat			
Color	Assorted colors			
Application for	Concrete, cement, mortar			
Components	Single Pack			
Volume solids	53% - 56% (White)			
Recommended dry film thickness	50µm			
Coats	2-3 Coats			
Thoretical coverage	6-8m²/L (@D.F.T 50μm)			
Dryling times at	5° C 20° C 40° C			
Dry through	3hrs 2hrs 0.5hrs			
Dry to recoat	9hrs 6hrs 4hrs			
Thinning ratio	The paint ready to use after proper stirring water Add maximum 10%			
Thinner	Water			
Shelf life	1 Year from manufacture's date when stored In doors at 20-38 ^o C			

Disclaimer. All representations and recommendations set forth are given in good faith and the best of our knowledge. However due to varying conditions and applications the buyer shall conduct its own tests of this product before use. Under no circumstances will the manufacturer be liable for any loss or damages caused by incorrect usage. The sale of this product shall be on terms and conditions set forth on BOTICA's order acknowledgement

RECOMMENDED USES:

For use decorative exterior and interior walls concrete, cement mortar and masonry surface

SURFACE PREPARATION

- The wall concrete must be clean, free from dirt, sand, oil and greas. Make sure surface to be smooth.

- Don't apply during wet weather and surface moisture levels with wall are acceptable level before painting.

APPLICATION METHODS

-Spray : Machine must suitable to spray emulsion and dilute the paint with water 20%.

-Brush : Recommended to use soft brush and dilute the paint with water 10%.

-Roller : Recommended to use soft roller and dilute the paint with water 10%.

RECOMMENDED TYPICAL PAINT SYSTEM

NEW SURFACE		OLD SURFACE	
Exterior	Interior	Exterior	Interior
- C-Plast 03 layers	- C-Plast 03 layers	- Crack Shield 01 Coat	- Crack Shield 01 Coat
- Stick shield 01 Coat	- Wall Stick 01 Coat	- C-Plast 03 layers	- C-Plast 03 layers
- Water Shield 02Coats	- Gloss Shield 02 Coats	- Stick shield 01 Coat	- Wall Stick 01 Coat
		- Water Shield 02 Coats	- Gloss Shield 02 Coats

PACKACHING

Water Shield : 19Litres/ 5US Gallon

: 05Litres/ 1US Gallon

CONDITION DURING APPLICATION

Sharking or mixing paint with machine 2mininutes before dilute with water and paint apply under temperature from 10° C to 45° C. The temperature should be measured in the vicinity of the substrate.

Disclaimer. All representations and recommendations set forth are given in good faith and the best of our knowledge. However due to varying conditions and applications the buyer shall conduct its own tests of this product before use. Under no circumstances will the manufacturer be liable for any loss or damages caused by incorrect usage. The sale of this product shall be on terms and conditions set forth on BOTICA's order acknowledgement

STORAGE AND SHELF LIFE

Please store with dry place and should be with temperature 20°C to 35°C, in an elevated condition.

HEALTH AND SAFETY

Please observe the precaution displayed the container from away with child, food, drinks, animals and container must be ventilated. If any immediately emergency use water and consult with doctor. Avoid skin contact and eyes should be use glove and eyes glass.

Disclaimer. All representations and recommendations set forth are given in good faith and the best of our knowledge. However due to varying conditions and applications the buyer shall conduct its own tests of this product before use. Under no circumstances will the manufacturer be liable for any loss or damages caused by incorrect usage. The sale of this product shall be on terms and conditions set forth on BOTICA's order acknowledgement