

Technical Data Sheet

Craver Premium Gloss

Product description

Type

A premium gloss paint by top coat and primer can be in one application for all surfaces, for decorative on multi-substrates such as wood, metal and specially galvanized steel. This high quality acrylic solvent based paint specially formulated for interior, exterior protection. It offers high gloss film, quick drying and excellent adhesion.

Features and benefits

Excellent Colour Last - Durable colours and high gloss that keeps the property looking new over time for a longer period.

Quick Drying Time - Drying time is quick touch dry after application making the property ready for occupancy in shorter time

Good Covering - High hiding power .

Excellent Adhesion - Durable lasting and prevents against growth of surface anti-rust, fungus and abrasive in aggressive environment.

Recommended use

Application for Interior and exterior surfaces, suitable for both new or painted substrate.

Substrate

On wood, metal and galvanized steel surfaces.

Product data

Packaging size : There are three different packed size which are 1L, 4L, 19L
Colours : As per colour card of Botica(Cambodia) Co., Ltd

Application data

Remarks

Handle with care. Mix paint well before use.

Application Method

Application Tools : Spray gun, brush, roller
Dilution thinner : Botica thinner
Dilution ratio : Maximum 10-15%

Application Instruction

Spray, brush in a well ventilation area.
Do not apply when temperature is lower than 15 degree C or himidity is higher than 85%
Surface temperature must be 3 degree higher than the dew point.
Refer to TDS carefully before applying.

Physical Properties

Theoretical coverage	: 8-10m ² /Litre/coat approx.
Drying time	: Touch dry : 10-15mins
Gloss (60 ⁰ angle)	: Minimum 90 GU (ASTM D523)
Hardness	: Maximum HB (ASTM 3363)

Directions for use

Surface preparation

The surface must be dry and clean, free from rust, dust, oil, grease or waxy contamination.

Any rust or mill scale must be completely removed.

*Old surfaces : Remove old coating and clean the surface to be free from dust and dirt, oil, wax and any contaminants.

*New surfaces : Clean the surface to be free from dust, dirt, oil, wax and contaminants.

Recommended paint system

Spray or brush 1-2 coats

Storage and shelf life

Maximum 4 years in sealed container.

Store in well-ventilated and shaded area. Keep the container in upright position with tightly closed lid.

Keep away from heat. Spark and open flame.

Keep out of the reach of children

Health and safety

Wear mask, gloves, goggles when applying paint. Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. It becomes prohibited to smell, taste, drink paint, smoke while pour or mix paint. Dispose of any waste in accordance with the appropriate local regulations. This product is suitable for application on materials, don't use for human and animals.

Disclaimer

This information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything other than the quality of the product itself.

We reserve the right to change the given data without notice.